

CO395Flex™ Certification Oven

Description

The **CO395Flex™ Certification Oven** is a stand alone version of the permeation tube oven used in the KIN-TEK 401M, Module Gas Standards Generating System.

Typically a gas standards generator such as the FlexStream™ or 491M is used routinely, or intermittently for creating several different applications. But permeation tubes require several hours for the emission rate to stabilize after a temperature change. The **CO395Flex™** is a compact, economical unit designed to maintain permeation tubes in a constantly equilibrated state, ready for immediate use in each application. This feature is especially useful for standards laboratories where the weight loss rate of the tube(s) is continually monitored to insure accuracy, or when permeation tubes are unexpectedly needed to trouble shoot an analyzer. It also saves hours of calibration time by providing pre-heated tubes ready for immediate use.

Features

The **CO395Flex™** features open frame construction for easy access to the permeation tube. An onboard constant-differential-pressure flow controller insures constant flow over the permeation tube. Temperature can be controlled at any value from approximately 30 °C (at least 5 °C above ambient temperature) to 150 °C. Temperature settings are NIST traceable to ± 0.1 °C to insure minimum upset when changing applications.



Technical Information

Dimensions: 9" wide x 5 ¼" deep x 8" high

Weight: Approx. 5 ½ lb.

Power: 115 , 1 A peak (230V optional)

Temperature Ranges: Typically 30° (5 °C above ambient) to 150 °C; digitally set in 0.1 °C increments.
(no temperature indication)

Flow: Typically 100 cc/min. Adjustable from 20 cc/min. to 200 cc/min. (no flow indication)

Tube Capacity: Accepts disposable permeation tubes, KIN-TEK refillable tubes, and diffusion tubes.
Holds up to 8 disposable tubes, one refillable tube, or 1-2 diffusion tubes.

Represented by:

KIN-TEK 

The Calibration Specialists

1-800-326-3627
Ph: (409) 938-3627
Fax: (409) 938-3710
www.kin-tek.com
email: sales@kin-tek.com

Rev CO395Flex.02122017
Copyright© 2016 KIN-TEK Analytical, Inc.
All rights reserved. Printed in USA